

# Declaration of Performance

## T4305FPCPR

1. Unique identification code of the product-type:  
Power-teK WM 660 GGN, Power-teK WM 660 GSN, Power-teK WM 660 SSN, Power-teK WM 660 GGA, Power-teK WM 660 GSA, Power-teK WM 660 SSA, Power-teK FM 100, Power-teK FM 660, Power-teK FM 100 ALU, Power-teK FM 660 ALU, Fire-teK WM 910 GGA, Fire-teK WM 910 GGN, Power-teK WM 660 GGV, Fire-teK WM 910 GGB, Fire-teK FM 910 ALB
2. Intended use or uses:  
Thermal Insulation products for building equipment and industrial installations
3. Manufacturer:  
Knauf Insulation d.o.o.  
Varaždinska 140, 42220 Novi Marof  
Croatia  
www.knaufinsulation.com - dop@knaufinsulation.com
4. Authorised representative:  
Not applicable
5. System or systems of assessment and verification of constancy of performance:  
AVCP System 1 for Reaction to Fire  
AVCP System 3 for the other characteristics
- 6a. Harmonized Standard:  
EN 14303:2009 + A1:2013  
  
Notified body or bodies:  
AVCP System 1: (Notified certification body) 0751 - Forschungsinstitut für Wärmeschutz e. V. München  
FIW München - - -  
  
AVCP System 3: (Notified testing laboratory) 0751 - Forschungsinstitut für Wärmeschutz e. V. München  
FIW München - - - - - - - -
- 6b. European Assessment document: not applicable  
European Technical Assessment: not applicable  
Technical Assessment Body: not applicable  
Notified body/ies: not applicable
7. Declared Performances:  
See next page

| Essential Characteristics                                   | T4305FPCPR   |                     | Harmonised Technical Standard |
|---|--|---------------------|-------------------------------|
|   | Performance  | Fire-teK FM 910 ALB |                               |
| Reaction to fire  | Reaction to fire   | A1                  | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                 |                               |
| Water Permeability  | Water Absorption   | WS1                 |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                 |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                 |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10               |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                 |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                 |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}             |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}             |                               |
|   | Dimensional Stability  | NPD                 |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
|   | Durability characteristics                                   | NPD                 |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}             |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}             |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                     | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                  | 0,040                         |
|   |  | 100                 | 0,046                         |
|   |  | 200                 | 0,060                         |
|   |  | 300                 | 0,079                         |
|   |  | 400                 | 0,102                         |
|   |  | 500                 | 0,131                         |
|   |  | 600                 | 0,166                         |
|   |  | 660                 | 0,190                         |
| NPD   | NPD  |                     |                               |
| NPD - No performance determined                             |  |                     |                               |

| Essential Characteristics                                   | T4305FPCPR   |                     | Harmonised Technical Standard |
|---|--|---------------------|-------------------------------|
|   | Performance  | Fire-teK WM 910 GGA |                               |
| Reaction to fire  | Reaction to fire   | A1                  | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                 |                               |
| Water Permeability  | Water Absorption   | WS1                 |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                 |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                 |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10               |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                 |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                 |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}             |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}             |                               |
|   | Dimensional Stability  | NPD                 |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
|   | Durability characteristics                                   | NPD                 |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}             |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}             |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                     | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                  | 0,040                         |
|   |  | 100                 | 0,046                         |
|   |  | 200                 | 0,060                         |
|   |  | 300                 | 0,079                         |
|   |  | 400                 | 0,102                         |
|   |  | 500                 | 0,131                         |
|   |  | 600                 | 0,166                         |
|   |  | 660                 | 0,190                         |
| NPD   | NPD  |                     |                               |
| NPD - No performance determined                             |  |                     |                               |

| Essential Characteristics                                   | T4305FPCPR   |                     | Harmonised Technical Standard |
|---|--|---------------------|-------------------------------|
|   | Performance  | Fire-teK WM 910 GGB |                               |
| Reaction to fire  | Reaction to fire   | A1                  | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                 |                               |
| Water Permeability  | Water Absorption   | WS1                 |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                 |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                 |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10               |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                 |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                 |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}             |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}             |                               |
|   | Dimensional Stability  | NPD                 |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
|   | Durability characteristics                                   | NPD                 |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}             |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}             |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                     | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                  | 0,040                         |
|   |  | 100                 | 0,046                         |
|   |  | 200                 | 0,060                         |
|   |  | 300                 | 0,079                         |
|   |  | 400                 | 0,102                         |
|   |  | 500                 | 0,131                         |
|   |  | 600                 | 0,166                         |
|   |  | 660                 | 0,190                         |
| NPD   | NPD  |                     |                               |
| NPD - No performance determined                             |  |                     |                               |

| Essential Characteristics                                   | T4305FPCPR   |                     | Harmonised Technical Standard |
|---|--|---------------------|-------------------------------|
|   | Performance  | Fire-teK WM 910 GGN |                               |
| Reaction to fire  | Reaction to fire   | A1                  | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                 |                               |
| Water Permeability  | Water Absorption   | WS1                 |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                 |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                 |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10               |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                 |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                 |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}             |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}             |                               |
|   | Dimensional Stability  | NPD                 |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
|   | Durability characteristics                                   | NPD                 |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}             |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}             |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C              |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                     | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                  | 0,040                         |
|   |  | 100                 | 0,046                         |
|   |  | 200                 | 0,060                         |
|   |  | 300                 | 0,079                         |
|   |  | 400                 | 0,102                         |
|   |  | 500                 | 0,131                         |
|   |  | 600                 | 0,166                         |
|   |  | 660                 | 0,190                         |
| NPD   | NPD  |                     |                               |
| NPD - No performance determined                             |  |                     |                               |

| Essential Characteristics                                   | T4305FPCPR   |   | Harmonised Technical Standard |
|---|--|---|-------------------------------|
|   | Performance  | Power-teK FM 100 ALU,<br>Power-teK FM 660 ALU |                               |
| Reaction to fire  | Reaction to fire   | A1  | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD   |                               |
| Water Permeability  | Water Absorption   | WS1   |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | MV1   |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD   |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10   |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD   |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD   |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}                                       |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}                                       |                               |
|   | Dimensional Stability  | NPD   |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C  |                               |
|   | Durability characteristics                                   | NPD   |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}                                       |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}                                       |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C  |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |   | 30 - 100 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50  | 0,040                         |
|   |  | 100   | 0,046                         |
|   |  | 200   | 0,060                         |
|   |  | 300   | 0,079                         |
|   |  | 400   | 0,102                         |
|   |  | 500   | 0,131                         |
|   |  | 600   | 0,166                         |
|   |  | 660   | 0,190                         |
| NPD   | NPD  |   |                               |

NPD - No performance determined

| Essential Characteristics                                   | T4305FPCPR   |                                    | Harmonised Technical Standard |
|---|--|------------------------------------|-------------------------------|
|   | Performance  | Power-teK FM 100, Power-teK FM 660 |                               |
| Reaction to fire  | Reaction to fire   | A1                                 | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                                |                               |
| Water Permeability  | Water Absorption   | WS1                                |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                                |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                                |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                              |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                                |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                                |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}                            |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}                            |                               |
|   | Dimensional Stability  | NPD                                |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C                             |                               |
|   | Durability characteristics                                   | NPD                                |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}                            |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}                            |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C                             |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                                    | 30 - 100 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                                 | 0,040                         |
|   |  | 100                                | 0,046                         |
|   |  | 200                                | 0,060                         |
|   |  | 300                                | 0,079                         |
|   |  | 400                                | 0,102                         |
|   |  | 500                                | 0,131                         |
|   |  | 600                                | 0,166                         |
|   |  | 660                                | 0,190                         |
| NPD   | NPD  |                                    |                               |
| NPD - No performance determined                             |  |                                    |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 GGA |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |



| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 GGN |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 GGV |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 GSA |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 GSN |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 SSA |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

| Essential Characteristics                                   | T4305FPCPR   |                      | Harmonised Technical Standard |
|---|--|----------------------|-------------------------------|
|   | Performance  | Power-teK WM 660 SSN |                               |
| Reaction to fire  | Reaction to fire   | A1                   | EN 14303:2009 + A1:2013       |
| Acoustic Absorption Index                                   | Sound Absorption   | NPD                  |                               |
| Water Permeability  | Water Absorption   | WS1                  |                               |
| Water Vapour Permeability                                   | Water Vapour Diffusion Resistance                            | NPD                  |                               |
| Compressive Strength  | Compressive Stress or Compressive Strength for Flat Products | NPD                  |                               |
| Rate of release of corrosive substances                     | Trace quantities of water-soluble ions and the pH-value      | CL 10                |                               |
| Release of Dangerous Substances to the indoor environment   | Release of Dangerous Substances                              | NPD                  |                               |
| Continuous glowing combustion                               | Continuous glowing combustion                                | NPD                  |                               |
| Durability of reaction to fire against ageing / degradation | Durability characteristics                                   | NPD {b}              |                               |
| Durability of thermal resistance against ageing/degradation | Thermal Conductivity   | NPD {c}              |                               |
|   | Dimensional Stability  | NPD                  |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
|   | Durability characteristics                                   | NPD                  |                               |
| Durability of reaction to fire against high temperature     | Durability characteristics                                   | NPD {d}              |                               |
| Durability of thermal resistance against high temperature   | Durability Characteristics                                   | NPD {c}              |                               |
|   | Maximum service temperature - dimensional stability          | 660 °C               |                               |
| Thermal Resistance  | Dimensions & Tolerances                                      |                      | 30 - 120 / T2                 |
|   | Thermal conductivity (W/mk) at Temperature in °C             | 50                   | 0,040                         |
|   |  | 100                  | 0,046                         |
|   |  | 200                  | 0,060                         |
|   |  | 300                  | 0,079                         |
|   |  | 400                  | 0,102                         |
|   |  | 500                  | 0,131                         |
|   |  | 600                  | 0,166                         |
|   |  | 660                  | 0,190                         |
| NPD   | NPD  |                      |                               |
| NPD - No performance determined                             |  |                      |                               |

8. Appropriate Technical Documentation and / or Specific Technical Documentation:

Not applicable


The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for an on behalf of the manufacturer by:

Stjepan Mršić - Plant manager

(Name and function)



Novi Marof - 19-11-21

(Place and date of issue)

Footnotes

{a} The requirement on a certain characteristic is not applicable in those Member States (MSs) where there are no regulatory requirements on that characteristic for the intended use of the product. In this case, manufacturers placing their products on the market of these MSs are not obliged to determine nor declare the performance of their products with regard to this characteristic and the option 'No performance determined' (NPD) in the information accompanying the CE marking (see ZS.3) may be used. The NPD option may not be used, however, where the characteristic is subject to a threshold level (thermal resistance (thermal conductivity and thickness)).

{b} The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic contents, which cannot increase with time.

{c} Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.

{d} The fire performance of mineral wool does not deteriorate with high temperature. The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.